



# DPX<sup>®</sup>-75

## FEATURES:

- DPX<sup>®</sup> fiber jacket provides excellent grip on winch drums and heat resistance
- 1/6th the weight of wire rope and it floats
- Firm round cross-section for superior winch performance
- Lightweight handling performance reduces mooring related injuries

## APPLICATIONS:

- Primary mooring lines for single or split drum winches
- Winch line for deep water lifting projects

## SPECIFICATIONS:

Specific Gravity:  
1.00

Elastic Elongation Percentage:

At % of break strength

10% 0.33%

20% 0.49%

30% 0.78%

Size Diameter INCHES	Size Circumference INCHES	Weight Per 100 FT. POUNDS	SRT MBS* POUNDS	Size Diameter MILLIMETERS	Weight Per 100 M KILOGRAMS	SRT MBS* METRIC TONS	ISO/BS EN919 MBS METRIC TONS
1-1/8 in.	3-1/2 in.	33.0 lbs.	113,000 lbs.	28mm	49.1 Kg	51.0 MT	56.7 MT
1-1/4 in.	3-3/4 in.	36.0 lbs.	135,000 lbs.	30mm	53.6 Kg	61.2 MT	68.0 MT
1-5/16 in.	4 in.	42.0 lbs.	149,000 lbs.	32mm	62.5 Kg	67.4 MT	74.8 MT
1-3/8 in.	4-1/8 in.	45.0 lbs.	167,000 lbs.	34mm	67.0 Kg	75.5 MT	83.9 MT
1-1/2 in.	4-1/2 in.	51.5 lbs.	189,000 lbs.	36mm	76.6 Kg	85.7 MT	95.3 MT
1-5/8 in.	5 in.	58.0 lbs.	225,000 lbs.	40mm	86.3 Kg	102.0 MT	113.0 MT
1-11/16 in.	5-1/4 in.	65.0 lbs.	252,000 lbs.	42mm	96.7 Kg	114.0 MT	127.0 MT
1-3/4 in.	5-1/2 in.	69.5 lbs.	275,000 lbs.	44mm	103.0 Kg	125.0 MT	138.0 MT
2 in.	6 in.	84.5 lbs.	329,000 lbs.	48mm	126.0 Kg	149.0 MT	166.0 MT

\*Spliced strength

## SOUTHWEST OCEAN SERVICES

5718 Armour Drive  
Houston, Texas 77020  
1-800-231-6687  
Fax: 713-671-2515

[www.swos.net](http://www.swos.net)



**Samson**  
THE STRONGEST NAME IN ROPE